SAFETY DATA SHEET

CLEENOL STAIN REMOVER 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CLEENOL STAIN REMOVER 1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses SPOT STAIN REMOVER FOR INK, PEN AND PAINT. SPRAY ONTO SURFACE, RUB GENTLY WITH A DAMP CLOTH. WASH AS NORMAL.

1.3. Details of the supplier of the safety data sheet

Supplier

Cleenol Group Ltd
Neville House
Beaumont Road
Banbury
Oxon OX16 1RB
UK
Tel : +44 (0)1295 251721
Fax : +44 (0)1295 269561
sales@cleenol.co.uk

Manufacturer

Cleenol Group Ltd
Neville House
Beaumont Road
Banbury
Oxon OX16 1RB
UK
Tel : +44 (0)1295 251721
Fax : +44 (0)1295 269561
sales@cleenol.co.uk

1.4. Emergency telephone number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards

Flam. Liq. 3 - H226

Health hazards

Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards

Not Classified

Classification (67/548/EEC or 1999/45/EC)

Xi;R36. R43. R10.

2.2. Label elements

Pictogram

CLEENOL STAIN REMOVER 1

Signal word Danger

Hazard statements

H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing vapour/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P280 Wear protective gloves.
P280 Wear eye protection.

Contains FATTY ALCOHOL ETHOXYLATE, ORANGE TERPENES

Supplementary precautionary statements

P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with national regulations.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PROPAN-2-OL	5-10%
CAS number: 67-63-0 **EC number:** 200-661-7	
Classification	**Classification (67/548/EEC or 1999/45/EC)**
Flam. Liq. 2 - H225	F;R11 Xi;R36 R67
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
STOT SE 3 - H336	

CLEENOL STAIN REMOVER 1

FATTY ALCOHOL ETHOXYLATE	5-10%
CAS number: 160901-19-9 **EC number:** —	

Classification	Classification (67/548/EEC or 1999/45/EC)
Eye Dam. 1 - H318 Acute Tox. 4 - H302	Xn;R22. Xi;R41.

ORANGE TERPENES	1-5%
CAS number: 5989-27-5 **EC number:** 227-813-5	

Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412	Xi;R38. R10,R43,R52/53.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Rinse nose and mouth with water. Get medical attention if any discomfort continues.

Ingestion

Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin contact

Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact

Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray, foam, dry powder or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

CLEENOL STAIN REMOVER 1

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

Storage class

Chemical storage.

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m3
Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m3

WEL = Workplace Exposure Limit

Ingredient comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Liquid.

Colour

Colourless.

Odour

Characteristic.

Initial boiling point and range

100°C @ 760 mm Hg

Relative density

0.91 @ 20°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability

Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO_2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg)

10,000.0

Inhalation

Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.

Ingestion

May cause discomfort if swallowed.

Skin contact

Liquid may irritate skin.

Eye contact

Irritating to eyes.

SECTION 12: Ecological Information

Ecotoxicity

Not regarded as dangerous for the environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

CLEENOL STAIN REMOVER 1

Road transport notes	Not classified.
Rail transport notes	Not classified.
Sea transport notes	Not classified.
Air transport notes	Not classified.

14.1. UN number

UN No. (ADR/RID)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	FLAMMABLE LIQUID, N.O.S. CONTAINS METHOXY PROPANOL
Proper shipping name (IMDG)	FLAMMABLE LIQUID, N.O.S. CONTAINS METHOXY PROPANOL
Proper shipping name (ICAO)	FLAMMABLE LIQUID, N.O.S. CONTAINS METHOXY PROPANOL
Proper shipping name (ADN)	FLAMMABLE LIQUID, N.O.S. CONTAINS METHOXY PROPANOL

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID subsidiary risk	
ADR/RID label	3
IMDG class	3
IMDG subsidiary risk	
ICAO class/division	3
ICAO subsidiary risk	

Transport labels

14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

14.5. Environmental hazards

14.6. Special precautions for user

EmS	F-E, S-E
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

CLEENOL STAIN REMOVER 1

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

Guidance

Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date	31/03/2015
Revision	2
Supersedes date	30/03/2015
SDS number	GR4
Risk phrases in full	
	R10 Flammable.
	R11 Highly flammable.
	R22 Harmful if swallowed.
	R36 Irritating to eyes.
	R38 Irritating to skin.
	R41 Risk of serious damage to eyes.
	R43 May cause sensitisation by skin contact.
	R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
	R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	
	H225 Highly flammable liquid and vapour.
	H226 Flammable liquid and vapour.
	H302 Harmful if swallowed.
	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H318 Causes serious eye damage.
	H319 Causes serious eye irritation.
	H336 May cause drowsiness or dizziness.
	H412 Harmful to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.